

### Product description

Lead Cover for concealed fitting

With integrated flexible cable to prevent cable breakage

Clamp/plug connector technology, 10-pin

One-sided switch box suitable for wood, metal and plastic profiles

The 10313-24 accessory set with 2 curved end pieces lends itself as an accessory for the switch box in wooden profiles

### Overview of Advantages

- Door and frames can be manufactured and supplied separately.
- A check can be carried out in the factory beforehand to ensure electrical components at this interface work properly.
- Door leaves and frames can be installed separately, meaning the fitter isn't required to know how to install electrical components.
- The clamp-plug connection on the frame side can be directly connected to the building's wiring without using a junction box.
- As this component is exposed to heavy use due to movement, a high-grade special cable in the cable transition ensures it has a long service life.
- Wear due to friction in the cable transition is eliminated.
- Door leaves and frames can easily be repaired separately with no electrical engineering skills required
- Interface with wiring in building - straightforward connection for maintenance and diagnosis devices, enabling the source of defects to be detected easily and quickly eliminated

### Scope of delivery

- Lead cover

### Technical data

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Contact resistance per signal        | 0,35 Ohm                            |
| Input operating voltage              | 24 V +20%                           |
| Max. current consumption             | 1 A 100% ED, 4 A max. 1 sec. 10% ED |
| Version                              | Plug-in device                      |
| Material spiral hose                 | Stainless steel                     |
| Material spiral hose                 | Stainless steel                     |
| Max. permissible horizontal rotation | 200 mm                              |
| Length                               | 519 mm / 180 mm                     |
| Length                               | 24 mm / 24 mm                       |
| Length                               | 33 mm / 19 mm                       |
| Cycles at 180 turns                  | 1000000                             |
| Signal transmission                  | 10-pin                              |

Article number 10314-20-----00

EAN-Number 4042203335622

